AdvantageDKE

Digital Keypad Economy



The **AdvantageDKE** line of digital keyless entry offers both post or single gang, surface mount configurations. All models are stand alone and have 100 fully programmable, four digit codes.

AdvantageDKE post mount models are housed in heavy metal, powder coated enclosures with stainless steel faceplates. A metal keypad is used providing years of trouble free use.

With a 100 code capacity, the **26-100L** and the **26-100sg** keypads are the perfect solution for many low cost installations.

AdvantageDKE



26-100L



26-100sq

General Specifications

- Input: 12-24 VAC or VDC
- Output: n/o or n/c contact 1 -9 second
- Operating temperature: -15 to 175 Fahrenheit
- 16 gauge stainless steel faceplate
- 16 gauge powder coated enclosure
- Dimensions:

26-100L: 5.25h x 4.00w x 3.00d 26-100sg: 4.50h x 2.75w x 0.75d

Ship weight: 5 lbs.

Relay Specs

| | DC Load | AC Load |
|------------------------|----------|------------|
| Contact Rating | 1A @ 24V | .5A @ 120V |
| Max. switching voltage | 150V | 220V |
| Max. carrying current | 2A | 2A |
| Max. switching power | 28W | 60VA |

Features

- 100 programmable four digit codes
- Programmable Personal Master Code
- Programmable Latch / Unlatch Code
- Night Light
- Variable relay output time: 1 − 9 seconds
- Audible tone
- Non-volatile memory
- Power consumption: 25mA @ 24VAC
- Limited two year warranty

Manufactured by:

American Access Systems, Inc 7079 S Jordan Rd. Unit 6 Centennial, CO 80112

ph: (800) 541-5677 fx: (303) 799-9756 www.americanaccess.com

Distributed by: